

Appl. No. 10/677,385

AMENDMENTS TO THE CLAIMS

1. (Currently Amended) A flat and pliable circuit board connector, comprising:

an indented body having a front surface, a rear surface, and a top open space to form an open trough extending from the front surface to the rear surface;

a ~~movable~~ pivotal upper lid liftable for opening and closing the open trough of the indented body;

a plurality of terminals insertable into the indented body;
and

a pair of anchor ~~plates~~ members coupling on a left side and a right side of the indented body;

wherein the ~~indented body has an open trough having an open~~ trough surface and which has an open space, a protrusive side rib
ribs formed respectively on a left side and a right side of the
open trough surface, a plurality of ditches ~~formed on the surface~~
extending through a top side of the open trough surface, and insert
troughs formed on a left side wall and a right side wall of the
indented body, ~~thereof,~~ each of the ditches having a wedge rib to
couple with each of the ~~terminal~~ terminals;

each of the terminals has a upper leg, a lower leg, a vertical
bridge section and a latch leg, the latch leg ~~being~~ is integrally
connected to a distal end of a rear section of the lower leg to
form a mortise slot with the lower leg, the bridge section bridging

Appl. No. 10/677,385

the upper leg and the lower leg to form a latch slot and a pivot slot opposite to the latch slot, wherein the latch slot formed between front sections of the upper leg and the lower leg and the bridge section, and the pivot slot formed between the rear sections of the upper leg and the lower leg and the bridge section, such that the mortise slot is engageable with the wedge rib to allow one of the ~~terminal~~ terminals to be wedge-wedged in the a corresponding ditch, and the latch slot to be exposed in the top open space of the indented body bordering by the side ribs, and the pivot slot being engageable with one end of the upper lid to allow the lid pivotally moved toward the latch slot;

the ~~movable~~ upper lid includes a plate in contact with top surfaces of the side ribs when the lid covering the open trough, closed for covering the indented body, the plate having a stub shaft-shafts extending respectively from a left side and a right side of a rear end of the plate, thereof and a plurality of flutes corresponding to the terminals wedged in the ditches of the indented body; and

each of the the anchor plate-members has a flat surface, insert pins integrally extending upwards from one side of the flat surface to couple with the insert troughs of the indented body, and a bracket arm having a notch integrally extending upwards from one end of the one side to couple with one of the stub shaft-shafts of

Appl. No. 10/677,385

the ~~movable~~-upper lid to form a fulcrum for opening and closing the ~~movable~~-upper lid.

2. (Currently Amended) The flat and pliable circuit board connector of claim 1, wherein the plate of the ~~movable~~-upper lid is covered by a metal shield plate to prevent electromagnetic interference (EMI).

3. (Currently Amended) The flat and pliable circuit board connector of claim 1, wherein the ~~movable~~-upper lid has a rear sloped end sloping downwards, each of the flutes have at least one flute having an axle located on a distal end of the flute opening thereof.

4. (Original) The flat and pliable circuit board connector of claim 3, wherein the upper leg of the terminal has a distal end on a rear section bending downwards to form a bent section.

5. (Original) The flat and pliable circuit board connector of claim 1, wherein the wedge rib of the indented body includes a front end and a rear end forming respectively a tongue-shaped tenon.

Appl. No. 10/677,385

6. (Original) The flat and pliable circuit board connector of claim 1, wherein the wedge rib of the indented body has a notch on the top surface thereof.

7. (Currently Amended) The flat and pliable circuit board connector of claim 1, wherein the plate of the ~~movable~~ upper lid has ~~respectively a retaining member~~ members respectively extending outwards and downwards from a left side and a right side of a front end thereof.

8. (Currently Amended) The flat and pliable circuit board connector of claim 7, wherein each of the retaining member ~~members~~ has a latch stub extending from one side thereof.

9. (Currently Amended) The flat and pliable circuit board connector of claim 2, wherein the plate of the ~~movable~~ upper lid has ~~respectively a retaining member~~ members respectively extending outwards and downwards from a left side and a right side of a front end thereof, ~~the~~ and each of the retaining member ~~members~~ having a latch stub extending from one side thereof.

10. (Currently Amended) The flat and pliable circuit board connector of claim 9, wherein the metal shield plate has ~~a rear flap~~ flaps located respectively on a left side and a right side of

Appl. No. 10/677,385

a rear end thereof, each of the rear flap-flaps having a latch notch ~~directing downwards~~.

11. (Currently Amended) The flat and pliable circuit board connector of claim 10, wherein each of the rear flap-flaps has a bulged spot extending from one side thereof.